

อุปกรณ์ประตูหนีไฟ

EXIT DEVICE
TOUCH BAR TYPE

UL 520

- Easily operated push rail for handicapped people used
- Clean styling & design in mechanism, fairly smooth operation, and easy installation.
- Quick release by light touching on the bar.
- Stainless steel cast latching, dead guarded bolt & operating cam, and providing long last life.
- Hex key dogging feature.
- Low profile end cap prevent being possible pushed off.

PRODUCT SPECIFICATIONS

For Doors	1-3/4" thick standard. Also usable on 1-3/8" to 2" thick doors (specify when other than 1-3/4" thick.) Door walls from 30° - 45°.
Cover	Lock Style Assembly - high density rust-resistant alloy.
Chassis	Lock Style Assembly - Steel or Stainless Steel.
Rail Assembly	Steel or Stainless Steel.
End Cap	Steel or Stainless Steel.
Latchbolt	Stainless Steel 3/4" throw deadlocking.
Dead Latch	Stainless Steel, 5/8"
Strikes	For 5/8" stop plus shim for 1/2" stop.
Springs	Stainless Steel.
Dogging	1/4" hex key type dogging standard.
Reversible	Not handed. Reversible for all functions and trims.
UL Listed	For Safety and Security.
ANSI Standard	ANSI 156.3 Grade 1.
Cylinders	Brass, rim-type, 7 pin, 2 Keys.
Finishes	Painted - Aluminum, Bronze, Duraodic. Stainless ; Highly polished or satin.



โซ้ค้อพ

TRIM ACCESSORIES
UL 520 SERIES

LH 520
Lever Handle

LE 520A
Lever X Escutcheon

LE 520B
Lever X Escutcheon

BK 520
Ball Knob

RC 520
Rim Cylinder

คานผล้ค

ลูลคบค

อุปกรณ์ประตูเหล็ก

ลูลคบค

โซ้ค้อพ



คคคคคค

HL530-DBL-PB

HL530-DBL-SS

HL530-SGL-AC